

## Cartridge filter HDF Series

Housing for general service including gasoline, diese, biodiesel, gases and more

Construction materials: Head in aluminium, body in SS 304, gaskets in Viton.

Designed for cartridges 6" (152 mm) OD, 3" (89 mm) ID, types microfilter, monitor, absorption and more. Adaptors for use with filter cartridges with other dimensions.

2 sizes, for cartridges with lengths 368 y 727 mm. Sizes 1 and 2



### General dimensions, mm.

Inlet & Outlet		2" BSP o NPT
Emptying		1/2" BSP
Vent		3/8" BSP
HV	Size 1	479
	Size 2	847
Volume	Size 1	9 litres
	Size 2	17 litres

Maximum service pressure 1 MPa

### Accessories included:

- Differential pressure gauge.
- Emptying valve.
- Vent valve.

### Options:

- Automatic vent valve.
- Diff. pressure gauge with switch.
- Service pressure 2 MPa
- Coupling for cartridges with different dimensions

### Design:

- EN13445 as standar
- ASME VIII Div. 1 as option

### CE Stamp

- Module A1 under PED97/23EC

**We have available housings for high flows also for use with filter cartridges with other dimensions.**

**Filtration experts since 1984**

All data are for informative purpose only they can change without prior notice

Hispano Europea de Comercio e Industria S.L.  
Calidad, 24 - Pol. Los Olivos - 28906 Getafe (Madrid) España  
Tel. (34) 916 967 039 Fax (34) 916 950 352  
e-mail: sales@hecisa.com <http://www.hecisa.com>

